

INTO A MULTIPURPOSE SOIL CONDITIONER

CULTIVATING - - - - Destroys roots and weeds, produces shallow, fine mulch to conserve moisture in the soil.

TILLING - - - - - - Mounted out in front, it gets under shrubs and into close quarters.

LEVELING - - - - - - Levels as it tills - tills as it levels.

AERATING - - - - - Keeps soil in healthy condition.

SEED BEDDING - - - - Produces a perfect seed bed with or without plowing.

MODEL 58 - 16 147.00
16" cutting width

MODEL 58 - 16 185.00

20" cutting width

SPECIFICATIONS MODEL 58

Cut width 16" or 20" Offset clearing right wheel Adjustable depth shoe Center plowshare Dust tight oil case Hardened bevel gears and sprockets No. 60 roller chain Splash lubrication Safety clutch set for 60 ft. lbs. Four bolts to attach

VERSATILE . LONG LIFE . FULLY GUARANTEED



MODEL 58 GC



To Reduce Ground Speed

When Slow Action is Needed

ALL SPEEDS ARE SELECTED BY A SIMPLE
ADJUSTMENT WITHOUT REMOVING

GEAR CASE OR WHEEL

Once Installed, Gearcase Need Never Be Removed.

dualulules 5300

Perfect mate for attachments like rotary tiller, snowplow, & others

SPECIFICATIONS

Hardened, steel cut gears

Heavy duty, grease retaining case Attaches quickly and easily

Uses standard (8 x 400) tires & rims Does not change

height of tractor Increases wheel tread only 2 inches

FLEXIBILITY

USING ONE GEARCASE - - - - 4 forward tractor ground speeds.

(Less than 1/2 original speed) 4 reverse tractor ground speeds.

USING TWO GEARCASES - - - 6 forward tractor ground speeds.

(Less than 1/4 original speed) 6 reverse tractor ground speeds.

MODEL 58 GC

MODEL 58 - 3GC
(A special gear set gives 2/3 original speed with one case.)

UNIVATOR, INC.

2035 CENTER STREET

BERKELEY, CALIFORNIA U.S.A.